

MATERIAL SAFETY DATA SHEET

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

PRODUCT

Product Name: GEAR LUBE 375 NC SPRAY CAN
Product Description: Hydrocarbons and Additives
Product Code: 201560400508, 611764-00, 977440
Intended Use: Aerosol lubricant

COMPANY IDENTIFICATION

Supplier: EXXON MOBIL CORPORATION
3225 GALLOWS RD.
FAIRFAX, VA. 22037 USA

24 Hour Health Emergency 609-737-4411
Transportation Emergency Phone 800-424-9300
ExxonMobil Transportation No. 281-834-3296
Product Technical Information 800-662-4525, 800-947-9147
MSDS Internet Address <http://www.exxon.com>, <http://www.mobil.com>

SECTION 2 COMPOSITION / INFORMATION ON INGREDIENTS

Reportable Hazardous Substance(s) or Complex Substance(s)

Name	CAS#	Concentration*
ASPHALT (PETROLEUM)	8052-42-4	30 - 40%
Butane	106-97-8	5 - 10%
HYDROTREATED LIGHT DISTILLATE	64742-47-8	5 - 10%
N-HEPTANE	142-82-5	20 - 30%
Naphthenic acids, zinc salts	12001-85-3	1 - 5%
Propane	74-98-6	10 - 20%
STRAIGHT-RUN MIDDLE DISTILLATES	64741-44-2	5 - 10%

* All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

SECTION 3 HAZARDS IDENTIFICATION

This material is considered to be hazardous according to regulatory guidelines (see (M)SDS Section 15).

POTENTIAL PHYSICAL / CHEMICAL EFFECTS

Flammable Gas. Material can release vapors that readily form flammable mixtures. Vapor accumulation could flash and/or explode if ignited. Suffocation (asphyxiant) hazard - if allowed to accumulate to concentrations that reduce oxygen below safe breathing levels. Material can accumulate static charges which may cause an ignition.

POTENTIAL HEALTH EFFECTS

Irritating to skin. May be irritating to the eyes, nose, throat, and lungs. Vapors may cause drowsiness and dizziness. Simple asphyxiant: Acts by displacing oxygen in the lungs thereby diminishing the supply of oxygen available to the blood and tissues. Symptoms include shortness of breath, rapid heart rate, incoordination, lethargy, headaches, nausea, vomiting, and disorientation. Continued lack of oxygen may result in convulsions, loss of consciousness and death. Since exercise increases the tissue need for oxygen, symptoms will occur more quickly during exertion in an oxygen-deficient environment. Oxygen in enclosed

Product Name: GEAR LUBE 375 NC SPRAY CAN

Revision Date: 14 Jan 2010

Page 2 of 12

spaces should be maintained at 21 percent by volume.
May cause central nervous system depression.

Target Organs: Skin |

ENVIRONMENTAL HAZARDS

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

NFPA Hazard ID:	Health: 1	Flammability: 4	Reactivity: 1
HMIS Hazard ID:	Health: 1	Flammability: 4	Reactivity: 1

NOTE: This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

SECTION 4 FIRST AID MEASURES

Inhalation

Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

Skin Contact

Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse.

EYE CONTACT

Flush thoroughly with water. If irritation occurs, get medical assistance.

Ingestion

Seek immediate medical attention. Do not induce vomiting.

SECTION 5 FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Appropriate Extinguishing Media: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

Inappropriate Extinguishing Media: Straight Streams of Water

FIRE FIGHTING

Fire Fighting Instructions: Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

Product Name: GEAR LUBE 375 NC SPRAY CAN

Revision Date: 14 Jan 2010

Page 3 of 12

Unusual Fire Hazards: Extremely Flammable. This liquid is volatile and gives off invisible vapors. Hazardous material. Firefighters should consider protective equipment indicated in Section 8. Aerosol cans involved in fire may rupture and become projectiles.

Hazardous Combustion Products: Smoke, Fume, Aldehydes, Sulfur Oxides, Incomplete combustion products, Oxides of carbon

FLAMMABILITY PROPERTIES

Flash Point [Method]: <-18C (0F) [Typical]

Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D

Autoignition Temperature: N/D

SECTION 6

ACCIDENTAL RELEASE MEASURES

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. US regulations require reporting releases of this material to the environment which exceed the applicable reportable quantity or oil spills which could reach any waterway including intermittent dry creeks. The National Response Center can be reached at (800)424-8802.

SPILL MANAGEMENT

Land Spill: Stop leak if you can do it without risk. Do not direct water at spill or source of leak. Prevent entry into waterways, sewer, basements or confined areas. If possible, turn leaking containers so that gas escapes rather than liquid. Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material. Ventilate the area. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Water Spill: Stop leak if you can do it without risk. Warn other shipping. Remove from the surface by skimming or with suitable absorbents. See Land Spill section of the (M)SDS for advice for gases.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

ENVIRONMENTAL PRECAUTIONS

Prevent entry into waterways, sewers, basements or confined areas.

SECTION 7

HANDLING AND STORAGE

HANDLING

Contents under pressure. Do not puncture. Avoid contact with skin. Prevent exposure to ignition sources, for example use non-sparking tools and explosion-proof equipment. Potentially toxic/irritating fumes/vapors may be evolved from heated or agitated material. Use only with adequate ventilation. Material can accumulate static charges which may cause an electrical spark (ignition source).

Static Accumulator: This material is a static accumulator.

STORAGE

Product Name: GEAR LUBE 375 NC SPRAY CAN

Revision Date: 14 Jan 2010

Page 4 of 12

Store in a cool, dry place with adequate ventilation. Keep away from incompatible materials, open flames, and high temperatures. Keep container closed. Handle containers with care. Open slowly in order to control possible pressure release. Store in a cool, well-ventilated area. Outside or detached storage preferred.

Storage Temperature: < 48°C (118°F)

SECTION 8	EXPOSURE CONTROLS / PERSONAL PROTECTION
------------------	--

EXPOSURE LIMIT VALUES

Exposure limits/standards (Note: Exposure limits are not additive)

Source	Form	Limit / Standard			NOTE	Source
ASPHALT (PETROLEUM) [benzene solubles]	Inhalable fraction.	TWA	0.5 mg/m3		N/A	ACGIH
Butane		TWA	1000 ppm		N/A	ACGIH
HYDROTREATED LIGHT DISTILLATE [total hydrocarbon vapor]	Non-Aerosol	TWA	200 mg/m3		Skin	ACGIH
N-HEPTANE		TWA	2000 mg/m3	500 ppm	N/A	OSHA Z1
N-HEPTANE		STEL	500 ppm		N/A	ACGIH
N-HEPTANE		TWA	400 ppm		N/A	ACGIH
Propane		TWA	1800 mg/m3	1000 ppm	N/A	OSHA Z1
Propane		TWA	1000 ppm		N/A	ACGIH
STRAIGHT-RUN MIDDLE DISTILLATES	Stable Aerosol.	TWA	5 mg/m3		N/A	ExxonMobil
STRAIGHT-RUN MIDDLE DISTILLATES	Vapor.	TWA	200 mg/m3		N/A	ExxonMobil

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

Use explosion-proof ventilation equipment to stay below exposure limits.

PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

No special requirements under ordinary conditions of use and with adequate ventilation.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode.

Product Name: GEAR LUBE 375 NC SPRAY CAN

Revision Date: 14 Jan 2010

Page 5 of 12

Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

Hand Protection: Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

If prolonged or repeated contact is likely, chemical resistant gloves are recommended. If contact with forearms is likely, wear gauntlet style gloves.

Eye Protection: Chemical goggles and face shield are recommended.

Skin and Body Protection: Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

If prolonged or repeated contact is likely, chemical, and oil resistant clothing is recommended.

Specific Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

ENVIRONMENTAL CONTROLS

See Sections 6, 7, 12, 13.

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

Typical physical and chemical properties are given below. Consult the Supplier in Section 1 for additional data.

GENERAL INFORMATION

Physical State: Gas
Form: Compressed or Liquified
Color: black
Odor: Petroleum/Solvent
Odor Threshold: N/D

IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

Relative Density (at 15 C): 0.78 - 0.79
Flash Point [Method]: <-18C (0F) [Typical]
Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D
Autoignition Temperature: N/D
Boiling Point / Range: -45C (-49F)
Vapor Density (Air = 1): N/D
Vapor Pressure: 343.872 kPa (2585.5 mm Hg) at 20 C
Evaporation Rate (N-Butyl Acetate = 1): > 37.5
pH: N/A
Log Pow (n-Octanol/Water Partition Coefficient): N/D
Solubility in Water: Negligible
Viscosity: N/D
Oxidizing Properties: See Hazards Identification Section.

Product Name: GEAR LUBE 375 NC SPRAY CAN
 Revision Date: 14 Jan 2010
 Page 6 of 12

OTHER INFORMATION

Freezing Point: N/D

Melting Point: N/A

SECTION 10	STABILITY AND REACTIVITY
-------------------	---------------------------------

STABILITY: Material is stable under normal conditions.

CONDITIONS TO AVOID: Avoid heat, sparks, open flames and other ignition sources.

MATERIALS TO AVOID: Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Material does not decompose at ambient temperatures.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11	TOXICOLOGICAL INFORMATION
-------------------	----------------------------------

ACUTE TOXICITY

<u>Route of Exposure</u>	<u>Conclusion / Remarks</u>
Inhalation	
Toxicity: No end point data.	Not determined.
Irritation: No end point data.	Elevated temperatures or mechanical action may form vapors, mist, or fumes which may be irritating to the eyes, nose, throat, or lungs. Based on assessment of the components.
Ingestion	
Toxicity: No end point data.	Minimally Toxic. Based on assessment of the components.
Skin	
Toxicity: No end point data.	Minimally Toxic. Based on assessment of the components.
Irritation: No end point data.	Moderately irritating to skin with prolonged exposure. Based on assessment of the components.
Eye	
Irritation: No end point data.	May cause mild, short-lasting discomfort to eyes. Based on assessment of the components.

CHRONIC/OTHER EFFECTS

For the product itself:

High vapor concentrations are irritating to the eyes and the respiratory tract, may cause headaches and dizziness, are anesthetic and may have other central nervous system effects.

Contains:

Asphalt: May contain low levels of polycyclic aromatic compounds (PACs), some of which are suspected of causing cancer under conditions of poor industrial hygiene and prolonged repeated contact. These PACs may also be inhaled. Inhalation studies at high concentrations of fumes resulted in bronchitis, pneumonitis, fibrosis and cell damage. Avoid contact with the asphalt and inhalation of vapor or aerosol from it.

Additional information is available by request.

Product Name: GEAR LUBE 375 NC SPRAY CAN

Revision Date: 14 Jan 2010

Page 7 of 12

The following ingredients are cited on the lists below:

Chemical Name	CAS Number	List Citations
ASPHALT (PETROLEUM)	8052-42-4	5

--REGULATORY LISTS SEARCHED--

1 = NTP CARC

2 = NTP SUS

3 = IARC 1

4 = IARC 2A

5 = IARC 2B

6 = OSHA CARC

SECTION 12 ECOLOGICAL INFORMATION

The information given is based on data available for the material, the components of the material, and similar materials.

ECOTOXICITY

Material -- Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

MOBILITY

More volatile component -- Highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.

High molecular wt. component -- Low water solubility, expected to sink and migrate into the sediment. Expected to partition to sediment and wastewater solids.

Components -- Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

PERSISTENCE AND DEGRADABILITY

Biodegradation:

A component -- Expected to be readily biodegradable.

Components -- Expected to be inherently biodegradable

High molecular wt. component -- Expected to be persistent.

Atmospheric Oxidation:

A component -- Expected to degrade rapidly in air

Components -- Expected to degrade at a moderate rate in air

BIOACCUMULATION POTENTIAL

Components -- Potential to bioaccumulate is low.

Majority of components -- Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

SECTION 13 DISPOSAL CONSIDERATIONS

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

DISPOSAL RECOMMENDATIONS

Contents under pressure. Do not puncture. Do not incinerate. Product is suitable for burning in an

Product Name: GEAR LUBE 375 NC SPRAY CAN

Revision Date: 14 Jan 2010

Page 8 of 12

enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products. Dispose of empty container as normal refuse.

REGULATORY DISPOSAL INFORMATION

RCRA Information: Disposal of unused product may be subject to RCRA regulations (40 CFR 261). Disposal of the used product may also be regulated due to ignitability, corrosivity, reactivity or toxicity as determined by the Toxicity Characteristic Leaching Procedure (TCLP). Potential RCRA characteristics: IGNITABILITY.

Empty Container Warning Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

SECTION 14

TRANSPORT INFORMATION

LAND (DOT)

Proper Shipping Name: **CONSUMER COMMODITY**
Hazard Class & Division: ORM-D
ID Number:
Packing Group: (N/A)
ERG Number:
Label(s): NONE
Transport Document Name: **CONSUMER COMMODITY, ORM-D**

LAND (TDG)

Proper Shipping Name: AEROSOLS, FLAMMABLE, N.O.S. (N-HEPTANE)
Hazard Class & Division: 2.1
UN Number: 1950
Packing Group: (N/A)

SEA (IMDG)

Proper Shipping Name: AEROSOLS (N-HEPTANE)
Hazard Class & Division: 2.1
EMS Number: F-D, S-U
UN Number: 1950
Packing Group: (N/A)
Marine Pollutant: Yes
Label(s): 2.1
Transport Document Name: **UN1950, AEROSOLS (N-heptane), 2.1, (-17.8°C c.c.), MARINE POLLUTANT**

AIR (IATA)

Proper Shipping Name: AEROSOLS, FLAMMABLE (N-HEPTANE)
Hazard Class & Division: 2.1
UN Number: 1950
Packing Group: (N/A)
Label(s) / Mark(s): 2.1, EHS
Transport Document Name: **UN1950, AEROSOLS, FLAMMABLE (N-heptane), 2.1**

Product Name: GEAR LUBE 375 NC SPRAY CAN

Revision Date: 14 Jan 2010

Page 9 of 12

SECTION 15	REGULATORY INFORMATION
-------------------	-------------------------------

OSHA HAZARD COMMUNICATION STANDARD: When used for its intended purpose, this material is classified as hazardous in accordance with OSHA 29CFR 1910.1200.

NATIONAL CHEMICAL INVENTORY LISTING: AICS, DSL, EINECS, TSCA

EPCRA: This material contains no extremely hazardous substances.

SARA (311/312) REPORTABLE HAZARD CATEGORIES: Fire. Pressure. Immediate Health.

SARA (313) TOXIC RELEASE INVENTORY:

Chemical Name	CAS Number	Typical Value
Naphthenic acids, zinc salts	12001-85-3	1 - 5%
ZINC NEODECANOATE	27253-29-8	1 - 5%

The following ingredients are cited on the lists below:

Chemical Name	CAS Number	List Citations
ASPHALT (PETROLEUM)	8052-42-4	1, 13, 16, 17, 18, 19
Butane	106-97-8	1, 13, 16, 17, 18, 19
HYDROTREATED LIGHT DISTILLATE	64742-47-8	1, 17, 18, 19
N-HEPTANE	142-82-5	1, 4, 5, 9, 13, 16, 17, 18, 19
Naphthenic acids, zinc salts	12001-85-3	13, 15, 17
Propane	74-98-6	1, 4, 13, 16, 17, 18, 19
STRAIGHT-RUN MIDDLE DISTILLATES	64741-44-2	17
ZINC NEODECANOATE	27253-29-8	13, 15, 17

--REGULATORY LISTS SEARCHED--

1 = ACGIH ALL	6 = TSCA 5a2	11 = CA P65 REPRO	16 = MN RTK
2 = ACGIH A1	7 = TSCA 5e	12 = CA RTK	17 = NJ RTK
3 = ACGIH A2	8 = TSCA 6	13 = IL RTK	18 = PA RTK
4 = OSHA Z	9 = TSCA 12b	14 = LA RTK	19 = RI RTK
5 = TSCA 4	10 = CA P65 CARC	15 = MI 293	

Code key: CARC=Carcinogen; REPRO=Reproductive

SECTION 16	OTHER INFORMATION
-------------------	--------------------------

N/D = Not determined, N/A = Not applicable

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

Revision Changes:

Product Name: GEAR LUBE 375 NC SPRAY CAN

Revision Date: 14 Jan 2010

Page 10 of 12

Section 04: First Aid Inhalation - Header was modified.
Section 04: First Aid Skin - Header was modified.
Section 04: First Aid Ingestion - Header was modified.
Section 06: Notification Procedures - Header was modified.
Section 10 Stability and Reactivity - Header was modified.
Section 13: Disposal Recommendations - Note was modified.
Section 09: Color was modified.
Section 09: Evaporation Rate - Header was modified.
Section 08: Personal Protection was modified.
Section 07: Handling and Storage - Handling was modified.
Hazard Identification: Physical/Chemical Hazard was modified.
Section 05: Hazardous Combustion Products was modified.
Section 06: Accidental Release - Spill Management - Water was modified.
Section 09: Relative Density - Header was modified.
Section 14: Transport Document Name was modified.
Section 14: Sea (IMDG) - Header was modified.
Section 14: Label(s) - Header was modified.
Section 14: Label(s) was modified.
Section 14: Transport Document Name was modified.
Section 14: Proper Shipping Name was modified.
Section 14: Transport Document Name was modified.
Composition: Component Table was modified.
Section 15: List Citations Table was modified.
Section 15: List Citation Table - Header was modified.
Section 15: SARA (313) TOXIC RELEASE INVENTORY - Table was modified.
Section 15: National Chemical Inventory Listing was modified.
Section 16: Precautions was modified.
Section 16: Water Spill was modified.
Section 16: Physical Hazards additional was modified.
Section 16: NA Contains was modified.
Section 06: Notification Procedures was modified.
Section 08: Exposure Limits Table was modified.
Section 11: Chronic Tox - Component was modified.
Section 09: Oxidizing Properties was modified.
Section 08: OEL Table - Notation Column - Header was modified.
Section 08: Exposure Limit Values - Header was modified.
Section 01: Company Contact Methods Sorted by Priority was modified.
Section 14: Marine Pollutant - Header was added.
Section 14: Marine Pollutant was added.
Section 14: IMO Technical Name - All was added.
Section 14: IATA Technical Name - All was added.
Section 14: TDG Technical Name - All was added.
Section 14: IMO Technical Name - Close parenthesis was added.
Section 14: IATA Technical Name - Close parenthesis was added.
Section 14: TDG Technical Name - Close parenthesis was added.
Section 14: IMO Technical Name - Open parenthesis was added.
Section 14: IATA Technical Name - Open parenthesis was added.
Section 14: TDG Technical Name - Open parenthesis was added.
Section 08: Exposure limits/standards was deleted.

PRECAUTIONARY LABEL TEXT:

Contains: Propane, N-HEPTANE, Butane

Product Name: GEAR LUBE 375 NC SPRAY CAN

Revision Date: 14 Jan 2010

Page 11 of 12

DANGER!

HEALTH HAZARDS

Irritating to skin.

Target Organs: Skin |

PHYSICAL HAZARDS

Flammable Gas. Suffocation (asphyxiant) hazard - if allowed to accumulate to concentrations that reduce oxygen below safe breathing levels. Material can accumulate static charges which may cause an ignition.

PRECAUTIONS

Contents under pressure. Do not puncture. Avoid contact with skin. Prevent exposure to ignition sources, for example use non-sparking tools and explosion-proof equipment. Potentially toxic/irritating fumes/vapors may be evolved from heated or agitated material. Use only with adequate ventilation.

FIRST AID

Inhalation: Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

Eye: Flush thoroughly with water. If irritation occurs, get medical assistance.

Oral: Seek immediate medical attention. Do not induce vomiting.

Skin: Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse.

FIRE FIGHTING MEDIA

Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

SPILL/LEAK

Land Spill: Stop leak if you can do it without risk. Do not direct water at spill or source of leak. Prevent entry into waterways, sewer, basements or confined areas. If possible, turn leaking containers so that gas escapes rather than liquid. Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material. Ventilate the area. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Water Spill: Warn other shipping. Remove from the surface by skimming or with suitable absorbents. See Land Spill section of the (M)SDS for advice for gases.

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.



Product Name: GEAR LUBE 375 NC SPRAY CAN

Revision Date: 14 Jan 2010

Page 12 of 12

Internal Use Only

MHC: 0, 0, 0, 0, 3, 1

PPEC: DVF

DGN: 2009266XUS (555041)

Copyright 2002 Exxon Mobil Corporation, All rights reserved